



NOTE:
 FIXINGS AND GASKET
 TO SUIT JOINT FLANGE
 ARE SUPPLIED INSIDE
 THE TANK.

DRAWINGS NO. **PW 454-2**

ALL DIMENSIONS ± 1mm UNLESS OTHERWISE STATED

SCALE **1:15**

CUSTOMER **CUSTOMER**

DATE **18/11/2010**

NOTES

All Purowater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and sealed correctly when water is contained within the tank.

TITLE **PW 454/2 TWO PIECE COLD WATER STORAGE TANK**

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE MOD

DATE A

NOTES

TANK SPECIFICATION:

INTERNAL DIMS 1067 x 610 x 710mm

EXTERNAL DIMS 1220 x 750 x 750mm

EACH SECTION DIMS 1220 x 750 x 365mm

NOM. CAPACITY 454 Litres

DRY WEIGHT 30kg

INSULATION 25mm

purowater storage ltd

Trusley Capital Farm
 Mableton
 Timeworth
 Sullis
 B78 2BU

Tel: 0121 323 4000
 Fax: 0121 323 4400
 www.purowaterstorage.co.uk