



**NOTE:**  
 FIXINGS AND GASKET  
 TO SUIT JOINT FLANGE  
 ARE SUPPLIED INSIDE  
 THE TANK.

DRAWING NO. **PW 680-2**

ALL DIMENSIONS ± 1mm UNLESS OTHERWISE STATED

SCALE **1:15**

CUSTOMER **A4**

CUSTOMER **N.DUDDY**

DATE **19/11/2010**

**NOTES**  
 All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and sealed correctly when water is contained within the tank.

TITLE **PW 680/2 TWO PIECE COLD WATER STORAGE TANK**

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	MOD	NOTES
	A	FIRST ISSUE

TANK SPECIFICATION:

INTERNAL DIMS	1220 x 815 x 610mm
EXTERNAL DIMS	1396 x 1091 x 650mm
EACH SECTION DIMS	1396 x 1091 x 315mm
NOM. CAPACITY	680 Litres
DRY WEIGHT	40kg
INSULATION	25mm

**purewater** storage ltd

Trusley Copples Farm  
 Medwellton  
 Timeworth  
 Sullis  
 B78 2BU

Tel: 0121 323 4000  
 Fax: 0121 323 4400  
 www.purewaterstorage.co.uk