



DRAWING NO.

PW 909-2

ALL DIMENSIONS ± 1mm UNLESS OTHERWISE STATED

SCALE 1:16

NOTES

All Purowater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and locked correctly when water is contained within the tank.

DRAWN BY S.SMITH  
CUSTOMER CUSTOMER

DATE 15/06/2008

TITLE

PW 909/2 TWO PIECE COLD WATER STORAGE TANK

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE MOD

DATE	MOD	NOTES
	A	FIRST ISSUE

TANK SPECIFICATION:

INTERNAL DIMS	1166 x 895 x 890mm
EXTERNAL DIMS	1344 x 1066 x 930mm
EXTERNAL DIMS	1344 x 1066 x 455mm
NOM. CAPACITY	909 Litres
DRY WEIGHT	50kg
INSULATION	25mm

**purewater storage ltd**

Trusley Coppice Farm  
Oxleden  
Medwell  
Tarnworth  
Sails  
B78 2BU

Tel: 0121 323 4000  
Fax: 0121 323 4400  
www.purewaterstorage.co.uk