



3 No 40mm Encapsulated RHS Steel Bracings

TITLE		NOTE: All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	DESCRIPTION: PW1125 one piece cold water storage tank c/w raised float valve housing to provide an AB Air gap	DATE	VERSION	NOTES
PW1125.INS.AB.6				22/10/2019	A	FIRST ISSUE
DRAWN BY	C.MORRIS	DATE	22/10/2019			
CUSTOMER	CUSTOMER	ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4	ALL DIMENSIONS IN MM - DO NOT SCALE		

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1500 x 500 x 1500mm
EXTERNAL DIMENSIONS	1665 x 665 x 1815mm
NOM. CAPACITY	1125 Litres
DRY WEIGHT	85 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP



SCALE:1:20 SHEET 1 OF 1