



TITLE		NOTE: All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
PW3000.INS.AG		
DRAWN BY	DATE	
C.MORRIS	05/12/2017	
CUSTOMER		
CUSTOMER		

DESCRIPTION:	
PW3000 one piece cold water storage tank suitable for AG/AF Air gap	
A4	

ALL DIMENSIONS IN MM - DO NOT SCALE	
-------------------------------------	--

DATE	VERSION	NOTES
26/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	3000 x 1000 x 1000mm
EXTERNAL DIMENSIONS	3202 x 1202 x 1093mm
NOM. CAPACITY	3000 Litres
DRY WEIGHT	195 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

SCALE:1:30 SHEET 1 OF 1