



TITLE	PW3001.INS.AG	
DRAWN BY	C.MORRIS	DATE 05/12/2017
CUSTOMER	CUSTOMER	

NOTE:	All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4

DESCRIPTION:	PW3001 one piece cold water storage tank suitable for AG/AF Air gap
ALL DIMENSIONS IN MM - DO NOT SCALE	

DATE	VERSION	NOTES
26/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :		
INTERNAL DIMENSIONS	2000 x 1000 x 1500mm	
EXTERNAL DIMENSIONS	2202 x 1202 x 1593mm	
NOM. CAPACITY	3000 Litres	
DRY WEIGHT	195 KG	
INSULATION THICKNESS	25mm	
WRAS CERT. NUMBER	131006	
MATERIAL	GRP	

SCALE: 1:30      SHEET 1 OF 1